Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies.



Zoeller Family of Water Solutions

MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347 SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961 (502) 778-2731 • 1 (800) 928-PUMP • FAX (502) 774-3624 SECTION: 3.10.010

FM0454 0514 Supersedes 0112

visit our web site: www.zoeller.com

# 910 SEWAGE SYSTEMS



Model 10-1494 shown.

OPTIONS: Zoeller recommends a High Water Alarm for added protection. See FM0732 for available models



Products may not be exactly as pictured.

## 910 - SIMPLEX & DUPLEX SEWAGE PACKAGE SYSTEMS (UNASSEMBLED)

Ideal for homes, farms, trailer courts, motels, restaurants and institutions where drain facilities are below existing sewer lines. Maximum Temperature rated at 130°F (54°C).

Model Number	Pump	Volts	Basin & Cover Uniche		Weight
910-0005*	M267	115V	Poly-Foam-18X30-2V2D	2" C.I.	77
910-0006*	D267	230V	Poly-Foam-18X30-2V2D	2" C.I.	77
910-0007*	M267	115V	Poly-Foam-18X30-3V2D	2" C.I.	77
910-0008*	D267	230V	Poly-Foam-18X30-3V2D	2" C.I.	77
910-0009†	M267	115V	Fiberglass-18X30-2V2D	2" C.I.	88
910-0016	M267	115V	Poly-18X30-2V2D	2" C.I.	83
910-0017*	M268	115V	Poly-Foam-18X30-3V3D	3" C.I.	92
910-0018*	M267	115V	Poly-18X30-2V2D	2" C.I.	82
910-0023	BN264	115V	Poly-18X30-2V2D	2" PVC	62
910-0024	BN267	115V	Poly-18X30-2V2D	2" PVC	76
910-0026	BN267	115V	Poly-Foam-18X30-2V2D	2" PVC	76
910-0030**	M264	115V	Duplex Poly-Foam-30X36-2V2D	2" Tri-check®	156
910-0031**	M267	115V	Duplex Poly-Foam-30X36-2V2D	2" Tri-check®	178

#### **BASINS** -

Polyethylene Structural Foam, Polyethylene or Fiberglass

#### **CHECK VALVES -**


2" Cast Iron and 2" PVC full flow design.

Consult factory for other combinations and prices, including 2" and 3" vertical discharge and vent, 115V or 230V. Polyethylene basins recommended for indoor installations only.

<sup>\*</sup> Split poly cover

<sup>†</sup> Split steel cover

<sup>\*\*</sup>Duplex System is complete with (2) automatic pumps, (1) Smart Pak Plus residential alternator, (1) 30" x 36" duplex poly-foam basin and (2) 2" Tri-checks (check valve, ball valve and union all-in-one).





## TOTAL DYNAMIC HEAD/FLOW PER MINUTE SEWAGE AND DEWATERING


MODELS		264		267/268	
Feet	Meters	Gal.	Liters	Gal.	Liters
5	1.5	90	341	128	484
10	3.1	60	227	89	337
15	4.6	23	87	50	189
20	6.1	-	-	10	38
Shut-off Head:		18 ft.	(5.5m)	21.5 ft.(6.6m)	

0099696

# **Duplex System for Indoor Applications (unassembled)**

## (2) 2" Tri-Check® Valves







### Duplex Basin with (2) Automatic Pumps







Indoor Sewage Applications Only 910-0030 (M264 - 4/10 HP) or 910-0031 (M267 - 1/2 HP) *includes:* 

- √ (2) Automatic Pumps (M264 or M267) Model Pumps
- √ (1) 10-0804 Smart Pak Residential Alternator with Alarm
- ✓ (1) 31-1105 30" X 36" Poly-foam Basin with 2" Vent /Discharge
- √ (2) 30-0101 Tri-Check® Valves