

ANYSTREAM® CLASSIC

Showerheads GENERAL SPECIFICATION

Water conserving pressure compensating Autoflo® device reduces flow to 2.5 GPM/9.46LPM maximum, to meet existing ASME A112.18.1/CSA B125.1 Standard. ½" N PT inlet.



S-2251

S-2251

Polished chrome plated Anystream® showerhead. Brass ball swivel joint. Brass shank. Spray adjusting handle. 3-1/2" face. 8 Lexan deposit resisting plungers with 64 spray channels.



S-2252

S-2252

Polished chrome plated Anystream® showerhead. Brass ball swivel joint. Brass shank. Spray adjusting peanut handle. 2-3/4" face. 6 Lexan deposit resisting plungers with 48 spray channels.



S-2253

S-2253

Polished chrome plated Anystream® showerhead. Brass ball swivel joint. Chrome plated shank. Spray adjusting T-handle. 2-1/4" face. 4 Lexan deposit resisting plungers with 32 spray channels.

OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> E2	2.0 GPM flow rate (S-2252 & S-2253 only)
<input type="checkbox"/> E175	1.75 GPM flow rate (S-2253 only)
<input type="checkbox"/> E15	1.5 GPM flow rate (S-2253 only)
<input type="checkbox"/> PB	Polished brass finish (S-2251 & S-2252 only)
<input type="checkbox"/> BP	Blister pack packaging (S-2252 & S-2253 only)
<input type="checkbox"/> BPT	½" British pipe thread inlet
<input type="checkbox"/> ORB	Oil rubbed bronze (S-2251 & S-2252 only)
<input type="checkbox"/> PN	Polished nickel finish (S-2251 & S-2252 only)
<input type="checkbox"/> BN	Brushed nickel finish (S-2251 & S-2252 only)

This space for Architect/Engineer approval. _____

